Emulsion Styrene-Butadiene Rubber



1ndiapol SBR-1502

Revised on: August 24, 2024

About Product:

Synthetic rubber Indiapol SBR-1502 is styrene and butadiene copolymer obtained by cold emulsion polymerization using the soaps of rosin and fatty acids. The polymer is stabilized by non-staining antioxidants. It provides excellent physical & process properties with good color characteristics.

Product Summary:		
Physical form	Light yellow colored bale wrapped in easily dispersible PE film.	
Packaging	Individual bales having weight ~35kg are wrapped in PE film. Product is available in returnable metal crates consisting of 36 bales or individual paper bag.	
Shelf Life	1 years from the date of manufacture.	
Storage condition	The product should be stored in its original packing at ambient temperature in dry conditions away from heat, ultraviolet or direct sun light.	
Safety Guidelines	Refer Safety Data Sheet for detailed information on product safety.	
Applications	Tyres, shoes material, belt, rubber clothing, roller, rubber floor and hoses.	

Product Specification:			
Parameters	Limit	Test Method	
Mooney viscosity ML 1+4 (100 °C), M	52 ± 6	ASTM D 1646	
Organic acids, % wt	4.75-7.00	ASTM D 5774	
Soap, % wt	0.50 max.	ASTM D 5774	
Bound styrene, % wt	23.5 ± 1.0	ASTM D 5775	
Volatile matter, % wt	0.75 max.	ASTM D 5668	
Ash content, % wt	0.75 max.	ASTM D 5667	
Compound properties (ASTM D 3185 Table 1A recipe), Curing 145 °C × 35 min:			
Tensile Strength, Kg/Cm ²	230 min.	ASTM D 412	
Modulus (300%), Kg/Cm2	180 ± 20	ASTM D 412	
Ultimate Elongation, %	330 min.	ASTM D 412	

Disclaimer: The information contained herein is believed to be true and accurate to the best of our knowledge and belief. However, ISRPL makes no warranty or guarantee, either expressed or implied and ISRPL would not be liable, in any way whatsoever, for the use of this information. Technical Advice furnished by ISRPL shall not constitute an express warranty, which is expressly disclaimed. All Technical Advice given is accepted at the risk of buyer. ISRPL disclaims any and all other warranties, whether express or implied, and whether arising by operation of law or otherwise, including, without limitation, any implied warranty of merchantability or fitness of the product for a particular purpose. ISRPL shall not be liable for consequential, incidental, punitive, special, exemplary or indirect damages, including but not limited to lost revenue, lost profits, business interruption, reduced output or losses arising from claims against buyer by buyer's customers. ISRPL's aggregate liability for any claim, demand, loss, injury, or damage, arising out of or in connection with use of this product shall be limited to the price payable or paid by.

Corporate Office: 1st Floor, Tower - 3, IGL Complex, Plot No. - 2B, Sector - 126, Noida - 201 304, Uttar Pradesh, India Tel: +91-120-4871000, Contact us: info@isrpl.co.in

Plant office: Opp. IOCL Naphtha Cracker Terminal Gate, Panipat Refinery, Panipat-132140, Haryana, India Tel: +91-180-259100